RED WING SHOES® I PETROKING" LT | DIRECT ATTACH CONSTRUCTION

Exceptional performance and value.



01 - FLEXGRIP PANEL
 Easy in and out, grips around the ankle for a great fit

o 02 - TREDMAX™ RUBBER OUTSOLE

Delivers exceptional slip resistance

03 — PREMIUM SAFETY TOECAP
 Lightwight, rugged nylon composite material meets
 EN and ASTM standards

 $\circ~$ 04 - FORCEGUARD $^{\otimes}$ Protects toe area from abrasion, oils and chemicals

• 05 - MADE IN ITALY

SPECIFICATIONS Safety Non-metallic Toe **Features** PR Puncture Resistant Electrostatic Dissipative Upper Full Grain Brown Leather Lining 3D Mesh Air Net Insole Lenzi PS5 Puncture Resistant with SD Shank Nylon Last RW51423 Construction Direct Attach **Ratings** EN ISO 20345:2011 S3 SRC HRO ASTM F2413-11, M/I/75/C/75, SD PR **EU Sizes** 36,37,38,39,40,41,42,43,44,45, 46,47,48 Origin Made in Italy **Technology** ForceGuard™ FlexGrip[™] Lenzi® ComfortGuard **Outsole** TredMax



Slip	Best
Oil/Gas	Best
Chemicals	Best
Abrasions	Best
Heat	Best
Non-Marking	Yes

HR

HEAT RESISTANT OUTSOLE Designed and tested to perform on high heat surfaces.

SRC

SLIP RESISTANCE RATED Meets SRC slip requirement.

FlexGrip™ Panel



EASY ON/OFF Heel expands to allow the back of foot to easily enter and exit



LOCKED-IN FIT Once you're in, heel contracts for a tight, comfortable fit



ANKLE SUPPORT Provides superior ankle support on the jobsite

