



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2022-02-08

Certificaat nummer/Cert no: EC26702185 rev. 0

ESAB ordernummer/Our order: 0100449927

Ordernummer/Your order: 20031729359

ESAB referentie/Our ref: M3PRD020

Referentie/Your ref:

Klantnummer/Cust no: NLB00033

Faxnummer/Your fax:

Orderdatum/Your date: 20220208

E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEERENVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address

Lasaulec Heerenveen
Kuper 4
HEERENVEEN
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

MV140110110

Hoeveelheid/Quantity: 20 KGM

PRODUCT/PRODUCT

Merk/Brand: ESAB

Omschrijving/Desc: OK Tigrod 19.49 2.0x1000mm 5kg

Artikelnummer/Item no: 194920R150

CLASSIFICATIES/CLASSIFICATIONS

SFA/AWS A5.7: ERCuNi

EN ISO 24373: S Cu 7158 (CuNi30Mn1FeTi)

CHEMISCHE SAMENSTELLING/ CHEMICAL COMPOSITION

Actual results: acc to EN 10204 - 3.1

Wire/strip

Overige/Auxiliary:

C	0.03%
Si	< 0.1%
Mn	0.8%
P	< 0.01%
S	< 0.01%
Ni	30.5%
Pb	0.001%
Ti	0.30%
Al	< 0.01%
Fe	0.54%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data: acc to EN 10204 - 2.2

Norm/Standard: As welded

Overige/Auxiliary:

Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2 Rm A4-A5

180 MPa 350 MPa 40 %

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Dariusz Kijowski

Quality Manager

Validation - Others

Per-Ake Bjornstedt, Joe Cacioppo