



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2016-11-25

Certificaat nummer/Cert no: EC24542167 rev. 0

ESAB ordernummer/Our order: 1496919
ESAB referentie/Our ref: Anita Frikk ESAB Kft.
Klantnummer/Cust no: NLB00033
Orderdatum/Your date: 20161121

Ordernummer/Your order: 20031368601
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEEREVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
LASAULEC HEERENVEEN
Lidnr. 403
KUPER 4
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

PV641505967

Hoeveelheid/Quantity:

2 PK

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK Autrod 12.64 0.8mm 15kg
Artikelnummer/Item no: 1264087700

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

Actual results: acc to EN 10204 - 3.1

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 636-A: W 46 3 W4Si1
EN ISO 636-A: W4Si1
EN ISO 14341-A: G 4Si1
EN ISO 14341-A: G 42 3 C1 4Si1
EN ISO 14341-A: G 46 4 M21 4Si1
SFA/AWS A5.18: ER70S-6

Wire/strip

Overige/Auxiliary:

C	0.08%
Si	0.95%
Mn	1.71%
P	0.012%
S	0.012%
Cr	0.04%
Ni	0.01%
Mo	< 0.01%
Cu	0.12%
V	< 0.01%
Al	< 0.01%
Ti+Zr	0.01%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPERTIES

Typical data: acc to EN 10204 - 2.2

Norm/Standard: EN
Overige/Auxiliary: M21
Toestand/Condition:

TREKPROEF/TENSILE

<u>ReL</u>	<u>Rm</u>	<u>A4-A5</u>
525 MPa	595 MPa	26 %

KERFSLAGWAARDE/IMPACT

<u>Temp</u>	+20 °C	-20 °C	-30 °C	-40 °C
<u>KV</u>	130 J	90 J	75 J	70 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Josef Moravek

Quality Manager

Validation - Others

Mikael Mimer

Product Manager