



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2019-03-14

Certificaat nummer/Cert no: EC25519514 rev. 0

ESAB ordernummer/Our order: 2190153
ESAB referentie/Our ref: Nicole Javaux France
Klantnummer/Cust no: NLB00033
Orderdatum/Your date: 20190312

Ordernummer/Your order: 20031525034
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEERENVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
LASAULEC HEERENVEEN
KUPER 4
LIDNR 403
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

PVT061821861

Hoeveelheid/Quantity: 1 PAC

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK Autrod 16.95 1.2mm 250kg
Artikelnummer/Item no: 1695129320

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

Actual results: acc to EN 10204 - 3.1

Wire/strip

Overige/Auxiliary:

C	0.04%
Si	0.8%
Mn	5.8%
P	0.03%
S	0.01%
Cr	18.0%
Ni	8.2%
Mo	0.2%
Cu	0.3%

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 14343-A: G 18 8 Mn
SFA/AWS A5.9: ER307 mod
Werkstoffnummer: ~1.4370

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data: acc to EN 10204 - 2.2

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2 Rm A4-A5
450 MPa 630 MPa 41 %

KERFSLAGWAARDE/IMPACT

Temp -60 °C
KV 56 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Josef Moravek

Quality Manager

Validation - Others

Peter Stones

Exaton Product Manager