



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2021-12-21

Certificaat nummer/Cert no: EC26660420 rev. 0

ESAB ordernummer/Our order: 0100419444
ESAB referentie/Our ref: Enikő Fekete
Klantnummer/Cust no: NLB00147
Orderdatum/Your date: 20211220

Ordernummer/Your order: 20031719267
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuraadres/Invoice address

ZEVIJ BV LASAULEC EMMEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address

LASAULEC EMMEN
JULES VERNEWEG 1
7821 AD EMMEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

PVV46113840

Hoeveelheid/Quantity: 12 PKM

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK Autrod 12.51 1.2mm 250kg
Artikelnummer/Item no: 1251129370
Heat No/Heat number:

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 14341-A: G 3Si1
EN ISO 14341-A: G 38 3 C1 3Si1
EN ISO 14341-A: G 42 4 M20 3Si1
EN ISO 14341-A: G 42 4 M21 3Si1
SFA/AWS A5.18: ER70S-6
CSA W48: B-G 49A 3 C1 S6
JIS Z 3312: YGW 12(C1)

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data: acc to EN 10204 - 2.2

Norm/Standard: EN
Overige/Auxiliary: M21 (EN ISO 14175)
Toestand/Condition: As Welded

TREKPROEF/TENSILE

ReL	Rm	A4-A5
470 MPa	560 MPa	26 %

KERFSLAGWAARDE/IMPACT

Temp	+20 °C	-20 °C	-30 °C	-40 °C
KV	130 J	120 J	100 J	90 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Josef Moravek

Quality Manager

Validation - Others

H. Rasmuson

Product Manager