



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2014-09-16

Certificaat nummer/Cert no: EC23588434 rev. 0

ESAB ordernummer/Our order: 922770
ESAB referentie/Our ref: Mariette Villieu
Klantnummer/Cust no: NLB00152
Orderdatum/Your date: 20140911

Ordernummer/Your order: 20031219257
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ B.V. LASAULEC CENTRAAL HVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
LASAULEC CENTRAAL B.V.
Lidnr. 400
KUPER 2
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

RB1429081

Hoeveelheid/Quantity:

41 CT

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK Autrod 5356 1.2mm 7kg
Artikelnummer/Item no: 1815129870

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

**Actual results
acc to EN 10204 - 3.1**

CLASSIFICATIES/CLASSIFICATIONS

SFA/AWS A5.10 ER5356
EN ISO 18273 S Al 5356 (AlMg5Cr(A))
JIS Z 3232 A53556

Wire/strip

Overige/Auxiliary:

Si	0.05%
Mn	0.14%
Cr	0.06%
Cu <	0.01%
Ti	0.07%
Al	94.0%
Fe	0.11%
Mg	5.0%
Zn <	0.01%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data

acc to EN 10204 - 2.2

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2	Rm	A4-A5
120 MPa	265 MPa	26 %

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

William Hamilton

Quality Assurance Manager

Validation - Others

Lance Vernam

Product Manager