



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2014-01-23

Certificaat nummer/Cert no: EC23299480 rev. 0

ESAB ordernummer/Our order: 757153
ESAB referentie/Our ref: Nicole Javaux France
Klantnummer/Cust no: NLB00034
Orderdatum/Your date: 20140113

Ordernummer/Your order: 20031170829
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC CENTRAAL HVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
Lasaulec Industrie
Bornholmstraat 10
9723 AX GRONINGEN
Netherlands

LEVERING/DELIVERY Lotnummer/Lot no: SB341293 Hoeveelheid/Quantity: 198 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 68.82 4.0x350mm 1/2 VP
Artikelnummer/Item no: 68824030G0

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

**Actual results
acc to EN 10204 - 3.1**

CLASSIFICATIES/CLASSIFICATIONS

EN 14700 E Fe11
EN ISO 3581-A E 29 9 R 1 2
SFA/AWS A5.4 (E312-17)
Werkstoffnummer 1.4337

All weld metal

Overige/Auxiliary:

C	0.15%
Si	1.10%
Mn	0.7%
P	0.022%
S	0.01%
Cr	29.1%
Ni	9.4%
Mo	0.24%
Cu	0.15%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

**Typical data
acc to EN 10204 - 2.2**

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

<u>Rp0.2</u>	<u>Rm</u>	<u>A4</u>
500 MPa	750 MPa	25 %

<u>Temp</u>	<u>KV</u>
+20 °C	40 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Ellen Björgran

Quality Manager

Validation - Others

Tapio Huhtala

Product Manager