



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2014-03-18

Certificaat nummer/Cert no: EC23369772 rev. 0

ESAB ordernummer/Our order: 798875
ESAB referentie/Our ref: Nicole Javaux France
Klantnummer/Cust no: NLB00152
Orderdatum/Your date: 20140306

Ordernummer/Your order: Various
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ B.V. LASAULEC CENTRAAL HVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
Lasaulec Centraal
Kuper 2
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY Lotnummer/Lot no: SB406122 Hoeveelheid/Quantity: 228 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 63.80 2.5x300mm 1/4 VP
Artikelnummer/Item no: 63802520L0

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

**Actual results
acc to EN 10204 - 3.1**

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 3581-A E 19 12 3 Nb R 3 2
SFA/AWS A5.4 E318-17
Werkstoffnummer 1.4576

All weld metal

Overige/Auxiliary:

C	0.02%
Si	0.81%
Mn	0.6%
P	0.018%
S	0.009%
Cr	17.4%
Ni	11.5%
Mo	2.9%
Nb	0.45%
Cu	0.09%
FN WRC-92	5

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

**Typical data
acc to EN 10204 - 2.2**

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2 Rm A5
500 MPa 620 MPa 35 %

KERFSLAGWAARDE/IMPACT

Temp KV
+20 °C 55 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Ellen Björgran

Quality Manager

Validation - Others

Tapio Huhtala

Product Manager