



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2015-03-18

Certificaat nummer/Cert no: EC23808021 rev. 0

ESAB ordernummer/Our order: 1041127
ESAB referentie/Our ref: Anita Frikk ESAB Kft.
Klantnummer/Cust no: NLB00033
Orderdatum/Your date: 20150311

Ordernummer/Your order: 20031255157
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC CENTRAAL HVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
LASAULEC HEERENVEEN
Lidnr. 403
KUPER 4
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

SB506030

Hoeveelheid/Quantity:

276 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 63.34 2.5x300mm 1/4 VP
Artikelnummer/Item no: 63342520L0

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

**Actual results
acc to EN 10204 - 3.1**

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 3581-A E 19 12 3 L R 1 1
SFA/AWS A5.4 E316L-16
CSA W48 E316L-16
Werkstoffnummer 1.4430

All weld metal

Overige/Auxiliary:

C	0.02%
Si	0.79%
Mn	0.8%
P	0.017%
S	0.005%
Cr	17.9%
Ni	11.9%
Mo	2.7%
Cu	0.06%
FN WRC-92	3

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

**Typical data
acc to EN 10204 - 2.2**

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2	Rm	A4
440 MPa	600 MPa	40 %

KERFSLAGWAARDE/IMPACT

Temp	KV
+20 °C	65 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Ellen Björgran

Quality Manager

Validation - Others

Tapio Huhtala

Product Manager