



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2021-03-01

Certificaat nummer/Cert no: EC26339616 rev. 0

ESAB ordernummer/Our order: 0100214785
ESAB referentie/Our ref: M3PRD020
Klantnummer/Cust no: NLB00033
Orderdatum/Your date: 20210226

Ordernummer/Your order: 20031660993
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEERENVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address

Lasaulec Heerenveen
Kuper 4
HEERENVEEN
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

SBU3510241

Hoeveelheid/Quantity: 342 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 73.08 2.5x350mm 1/4 VP
Artikelnummer/Item no: 73082531K0

CLASSIFICATIES/CLASSIFICATIONS

SFA/AWS A5.5: E8018-G
EN ISO 2560-A: E 46 5 Z B 32

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data: acc to EN 10204 - 2.2

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

Rp0.2 Rm A5
520 MPa 610 MPa 30 %

KERFSLAGWAARDE/IMPACT

Temp -50 °C
KV 100 J

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

Actual results: acc to EN 10204 - 3.1

All weld metal

Overige/Auxiliary:

C	0.06%
Si	0.54%
Mn	1.22%
P	0.010%
S	< 0.001%
Cr	0.02%
Ni	0.73%
Mo	< 0.01%
Cu	0.44%
V	< 0.01%

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Ellen Björger

Quality Manager

Validation - Others

J-P Ernoult

Product Manager