



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2021-02-03

Certificaat nummer/Cert no: EC26309345 rev. 0

ESAB ordernummer/Our order: 0100195232

Ordernummer/Your order: 20031655918

ESAB referentie/Our ref: M3PRD020

Referentie/Your ref:

Klantnummer/Cust no: NLB00033

Faxnummer/Your fax:

Orderdatum/Your date: 20210202

E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEERENVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address

Lasaulec Heerenveen
Kuper 4
HEERENVEEN
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

SBU5010089

Hoeveelheid/Quantity: 156 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 67.45 3.2x350mm 1/2 VP
Artikelnummer/Item no: **67453230T0**

CLASSIFICATIES/CLASSIFICATIONS

EN ISO 3581-A: E 18 8 Mn B 2 2
SFA/AWS A5.4: (E307-15)

CHEMISCHE SAMENSTELLING/ CHEMICAL COMPOSITION

Actual results: acc to EN 10204 - 3.1

All weld metal

Overige/Auxiliary:

C	0.09%
Si	0.3%
Mn	5.5%
P	0.015%
S	0.003%
Cr	19.0%
Ni	9.3%
Mo	0.11%
Cu	0.05%
N	0.04%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPS

Typical data: acc to EN 10204 - 2.2

Norm/Standard:

Overige/Auxiliary:

Toestand/Condition:

TREKPROEF/TENSILE

<u>Rp0.2</u>	<u>Rm</u>	<u>A5</u>
470 MPa	605 MPa	35 %

KERFSLAGWAARDE/IMPACT

<u>Temp</u>	+20 °C
<u>KV</u>	85 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Ellen Björgran

Quality Manager

Validation - Others

Tapio Huhtala

Product Manager