



KEURINGSRAPPORT (3.1) - Chemische samenstelling
FABRIEKS CONTROLE ATTEST (2.2) - Mechanische eigenschappen/
INSPECTION CERTIFICATE (3.1) - Chemical analysis
TEST REPORT (2.2) - Mechanical properties

Datum/Date: 2020-06-12

Certificaat nummer/Cert no: EC26054784 rev. 0

ESAB ordernummer/Our order: 0002512490
ESAB referentie/Our ref: Enik Fekete
Klantnummer/Cust no: NLB00033
Orderdatum/Your date: 20200611

Ordernummer/Your order: 20031609637
Referentie/Your ref:
Faxnummer/Your fax:
E-mail adres/Your e-mail:

Faktuuradres/Invoice address
ZEVIJ BV LASAULEC HEERENVEEN
POSTBUS 447
4900 AK OOSTERHOUT
Netherlands

Verzendadres certificaten/Cert receiver

Afleveradres/Delivery address
LASAULEC HEERENVEEN
KUPER 4
LIDNR 403
8447 GK HEERENVEEN
Netherlands

LEVERING/DELIVERY

Lotnummer/Lot no:

SFU17164

Hoeveelheid/Quantity:

5640 PCE

PRODUCT/PRODUCT

Merk/Brand: ESAB
Omschrijving/Desc: OK 53.16 SPEZIAL 3.2x350 1/2VP
Artikelnummer/Item no: **53163234G0**

**CHEMISCHE SAMENSTELLING/
CHEMICAL COMPOSITION**

Actual results: acc to EN 10204 - 3.1

CLASSIFICATIES/CLASSIFICATIONS

SFA/AWS A5.1: E7016
EN ISO 2560-A: E 38 2B 32 H10

All weld metal

Overige/Auxiliary:

C	0.08%
Si	0.61%
Mn	0.9%
P	0.021%
S	0.010%
Cr	< 0.1%
Ni	< 0.1%
Mo	< 0.1%
Nb	< 0.01%
Su	0.03%
V	0.01%

MECHANISCHE EIGENSCHAPPEN/MECHANICAL PROPERTIES
Typical data: acc to EN 10204 - 2.2

Norm/Standard:
Overige/Auxiliary:
Toestand/Condition:

TREKPROEF/TENSILE

ReL Rm A5
450 MPa 530 MPa 28 %

KERFSLAGWAARDE/IMPACT

Temp -20 °C
KV 90 J

OPMERKINGEN/COMMENTS

Product geleverd volgens een QA systeem welke voldoet aan de ISO 9001 norm.
Dit certificaat is elektronisch aangemaakt en geldig zonder ondertekening.
Voor vragen:

Esab Nederland BV - P.O. Box 2236 , 3800 CE Amersfoort , Nederland

Product supplied under a QA Programme fulfilling the EN ISO 9001 standard.
This certificate is produced electronically and is valid without signature.
Please refer any queries to: (see above)

Validation - Chemical Analysis

Bálint Bankó

Quality Assurance Manager

Validation - Others

J-P Ernout

Product Manager